


USL120045-2 12V 4.5Ah

3-5 Years Design Life



Plane Chart:

Unit:(mm) Terminal type:(F2)




Parameter Chart:


Volts		12V	
Capacity(25°C)	20 hours rate (0.225A)	4.5Ah	
Discharge Current Testing (25°C)	20 I ₂₀ rate (4.5A,27min)	30min	
	60 I ₂₀ rate (13.5A,7min)	7min	
Internal Resistance	Full Charged Battery 25°C	40mΩ	
Capacity Affected By Temperature	40°C	104%	
	25°C	100%	
	0°C	83%	
	-15°C	65%	
Residual Capacity (25°C)	Capacity After 3 Months Storage	91%	
	Capacity After 6 Months Storage	82%	
	Capacity After 12 Months Storage	65%	
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 1.35A Voltage 14.5~14.9V	
	Float (25°C)	Charge Voltage 13.6~13.8V	
Weight (Approx)		1.41Kg	

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.


Residual Capacity




Discharge Current 25°C



Constant voltage charging characteristics



Float Life



Constant Current Discharge Characteristics (A, 25°C)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	12.91	8.23	6.67	4.04	2.35	1.37	1.06	0.74	0.47	0.37	0.226
10.2V	10.96	7.81	6.40	3.93	2.26	1.34	1.04	0.73	0.46	0.37	0.225
10.5V	10.03	7.57	6.25	3.84	2.21	1.31	1.02	0.72	0.45	0.36	0.225
10.8V	9.20	7.33	6.07	3.73	2.15	1.28	1.00	0.71	0.44	0.35	0.218

Constant Current Discharge Characteristics (Watt, 25°C)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	139.40	89.74	73.33	45.22	26.78	15.70	12.13	8.36	5.90	4.97	2.65
10.2V	120.52	86.74	71.66	44.46	25.80	15.37	11.97	8.28	5.86	4.87	2.62
10.5V	111.35	84.78	70.63	43.79	25.36	15.30	11.81	8.16	5.83	4.76	2.59
10.8V	103.04	82.78	69.25	42.89	24.70	14.97	11.65	8.04	5.81	4.66	2.56

Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.

